Vikan - ultra microfibre technology







Vikan Easy Shine cloth, lustre cloth

				เนรแช เเบเา		
Article	Article no.	Size	Recommended frame or holder			
Lustre, blue	691543	400x400 mm	Spray bottle 581210			
Traceability	First 4 numbers describes the construction and the last numbers indicates the model of the product. Batch number indicates when					
	the product is manufactured, refering to this Vikan can trace the production and take action if necessary.					
Packed	5 pcs. in a plastic bag - 100 pcs. in a carton.					
CLEANING						
Where to use:	Cleaning of all types of hard surfaces with high demands on cleaning efficiency and hygienic. Perfect for cleaning					
	tiles, glasses, mirrors and windows. Avoid any contact with solvents, strong acid or alkaline products.					
How to use:	Preferably used in Vikan® system. A clean and dry cloth is to prefer - clean water in the spray bottle - spray on					
	visible spots and marks - wipe with the cloth - change when dirty - release in the laundry bag. Training is					
	organized by Vikan. Contact our sales organization for further information or set up a meeting.					
	organized by vikan. Contact our sales organization for further information or set up a meeting.					
Preparation:	No preparation, use dry and clean.					
Article	Dry weight ± 5 g	ml water	Damp w	eight maximum		
Lustre, grey	28					
Drying speed	The controlled adding of damp results in an uniform and quick drying surface. The cleaning result is very obvious					
	and immediate. Drops or stripes can be avoided.					
CARE	_					
		۸. ا				
	195/	(X ()				

Care label







Care label describes the maximum temperature that should be used. Due to cost, time and environmental impact a reduced temperature should always be evaluated depending on the application.

Recommended washing	70°C	Use detergents developed for microfiber products and with a pH less than 10. Softner or biocides should not be used as they can cause fiber damage and specific in combination with		
Washing in specific hygiene use	72-95°C, depending on time	high temperature. The electrostatic characteristic that is essential for the dust collecting will be reduced or lost with this type of treatment.		
Drying instruction	Max 55°C	The recommendation is made to avoid the textile to be damaged if humidity is not controlled.		
Autoclaveable	steam at 121° C	Possible to autoclave in steam if required. Other methods must be tested and approved by the originator.		
Disposal after use	Material recovery	The product is pure synthetic with high strength and can be used in many re-circulated materials depending on their specification.		
	Energy recovery	The fibers have a high energy value and can be totally burned without anything else than CO ₂ and water.		



		Vikan - ultra microfibre technology			
COMPOSITION					
Cleaning surface	80 % PES / 20 % PA. Splitted micro fiber: <0,3dtex	Fine knitted ultra microfibre provides large contact area between the cloth and cleaning surface. The more contact the better efficiency in the cleaning. On glass and mirrors where any spot is very visual, this type of flat construction is preferable. Fabric is provided with Vikan wicking performance which permanently protect the fibre and increase the transport inside the mop and enhance the cleaning and laundry efficiency.			
CHARACTERIST	ICS				
Shrinkage	Less than 10 % at recommended washing conditions.				
Absorbency	Fast and immediate wicking properties. Can easily keep 4x its own weight in moisture.				
Staining	No staining in dry or damp condition if recommendation is followed. Some staining can be noticed on other textiles when the higher temperature range is used but separate washing of mops and cloths that are of different construction or used fo different applications are recommended.				
GUARANTEE AN	ID PERFORMANCE				
	-	in general or hygiene use. Depending on cleaning areas (type of dirt and frequency of cleaning) the ecting the right mop and care, the life cycle can be optimized to even higher level. Ask our experts for			
Lenience	Our micro fibre construction is tested against several glossy surfaces to secure the leniency of the mops and cloths. But before use on specific sensitive surfaces check that no particles as sand or old dirt are kept in the textile. Use a CD or similar as a test surface if you are not convinced.				
DDODLIGT CC 17	URES AND BENEFI				
PRODUCT FEAT		TS			
Ergonomics		just spray and wipe			
Ergonomics Efficiency	Low weight - dry -				
Ergonomics	Low weight - dry -	just spray and wipe			



Developed by the Vikan group for professionals.



